

Multiflex Colourcoat AQ is a single pack synthetic polymer based emulsion coating, designed for both roofs and walls

Multiflex Colourcoat AQ is suitable for the treatment of all roof types, slates, concrete, asbestos sheeting, asphalt and bitumen types coverings. It is also suitable for timber, corrugated iron, lead flashings, glazing bars and all types of guttering.

PRODUCT ATTRIBUTES

- Easy to apply by either brush, roller or suitable spray
- Water based and therefore safe to use
- Available in a wide range of colours
- UV resistant
- Excellent colour stability
- Early cure water resistance

APPLICATION

Preparation:

Remove all loose debris, dirt, dust and unbounded material by sweeping, wet vacuum or pressure washing. Treat for algae or mildew as required with **Multiflex Fungicidal Wash**. Allow surface to dry thoroughly before starting work. Uneven surfaces or gap joints in the substrate must be avoided and corrected if present.

A cant strip is recommended at direction changes between horizontal and vertical surfaces. Install **Multiflex Reinforcing Fabric** over all lightweight and insulating concrete decks and over tongue and groove decks. Treat mechanical fasteners with **Multiflex Rustseal**, if rusty.

Install plywood in accordance with the manufacturer's recommendation, with all mechanical fasteners flush with the deck surface.

Unpainted metal must be washed with a de-greasing agent and thoroughly rinsed. Rust areas must be treated with **Multiflex Rustseal**.

Priming:

It is advisable to prime all porous surfaces with **Multiflex PU Primer**.

Application:

Apply **Multiflex Colourcoat AQ** with a 15mm nap roller at a rate of 0.4 lt/m². Allow to dry thoroughly. Apply a second coat no sooner than 12 hours later at a rate of 0.4lt/m².

Reinforce all flashings with fabric, embedded in and covered over, with Multiflex Colourcoat AQ (using above coverage rates). Multiflex Colourcoat AQ, should be protected from foot traffic during maintenance operations and other related activities. Do not install Multiflex Colourcoat AQ at temperatures below 5°C or above 40°C.

TECHNICAL SPECIFICATION @ 20°C

Setting Time	3 hours
S.G	1.2
Elongation	300%
Shore A	40
Coverage	0.4lt/m ² per coat
Cleaning tools	Clean with water
Packaging	5Lt & 25Lt

HEALTH & SAFETY

The product carries a No Hazard Classification

Morgan Polymers can give no product guarantee (either written or implied) due to the fact that application techniques vary and are totally outside their control.