

Repair Systems for Roofing – Multiflex Supercoat 50/Bituflex

Multiflex Supercoat 50 is a solvent based fibrous bitumen, which can be applied by brush or roller.

TECHNICAL SPECIFICATION @ 20°C

Multiflex Supercoat 50 is used to repair leaking roofs of all types, even whilst raining.

S.G	1.3
Drying Time	12 Hours
Water Resistance	Immediate
Coverage	1Kg/m ² per coat
Cleaning tools	Cleaning Solvent No1
Packaging	5Kg/15Kg

PRODUCT ATTRIBUTES

- Easy to apply straight from the can
- Can be applied during rainfall and even underwater
- Low cost
- Can be over treated with Multiflex Liquid Rubber Systems
- Can be applied to most roofing substrates
- Colours Black, or RAL 9007 grey aluminium.

HEALTH & SAFETY

See our Health & Safety data Sheet on **Multiflex Supercoat 50**

APPLICATION

All areas to be treated should be free of dirt, dust & grease. Any loose chippings should be removed. Fungal growth should be treated with Fungicidal Wash. Thoroughly stir the product and apply by soft broom direct from can. Large cracks and joints should be reinforced with reinforcing Fabric placed in coat 1 and sealed with coat 2.

Morgan Polymers can give no product guarantee (either written or implied) due to the fact that application techniques vary and are totally outside their control.